PCIe USB 3.0, NEC200, 1+1 Port

Art-Nr: 7070009

www.m-cab.de

Specification :

- Fully compliant with PCI Express Base Specification Revision 2.0
- Single - lane (x1) PCI Express throughput rates up to 5 Gbps
- Compliant with Universal Serial Bus 3.0 specification Revision 1.0
- Supports simultaneous operation of multiple USB 3.0, USB 2.0 and USB 1.1 devices
- Supports the following speed data rates as follows :
  Low-speed (1.5Mbps) / Full - speed (12Mbps) / High - speed (480Mbps) / Super-speed (5Gbps)
- Compliant with Intel's extensible Host Controller Interface (xHCI) Specification 0.96
- Supports 2 downstream ports for all speeds
- Built - in 4 - pin power connector for receiving extra power supply from system
- Hot - swapping feature allows you to connect / disconnect devices without powering down th system
- Support Windows® XP / Vista / 7 (32 / 64 bit)

System Requirements :
- Windows® XP / Vista / 7 (32 / 64 bit)
- One available PCI Express slot (Recommend PCI Express 2.0)

Accessories :

1 x Driver CD
1 x User Manual

Specifications are subject to change without prior notice. All tradenames referenced are registered namework of their respective owners.